

TransMix



The NEW TransMix TML 5.500



**The mobile screed factory –
as horizontal pneumatic air conveyor**

For semi-dry screeds

- Cement screed
- Calcium sulfate screed (anhydrite)
- Magnesia screed
- Vibrated floor (depending on consistency)



Your benefits

- The horizontal system enables even faster setup and installation on the construction site.
- The new TransMix operating concept features new software and hardware, including a display on the remote control and an optional touchscreen.
- The robust chassis is designed for heavy-duty use.
- Easy cleaning thanks to the proven quick-release fastener and always-on high-pressure cleaner.
- Maneuverable chassis with excellent handling characteristics – designed for durability and value retention.
- The hydraulic drive of the hose reel enables seamless, convenient setup of construction sites via remote control.

Why TransMix?



Consistently high quality

Consistently high screed quality is ensured by precise dosing of aggregates, binders, and additives.



Ease of work and comfort

Everything on board for an entire construction site. All work steps can be completed in just one trip and with two employees.

Further benefits

- **Easy handling**
- **High availability and service life**
- **Short payback time**
- **No material loss on the construction site, no unnecessary consumption of resources**
- **This means lower ancillary costs, as almost no disposal of waste and residual materials is required**

New operating concept and new user interface

Experience great operation
with the new TransMix
Ergonic® 3 user interface from
Putzmeister.

Brand New Hardware

The versatile combination of
rotary knob, buttons, and
optional touchscreen ensures
intuitive operation.

Improved Remote Control

Now also with a display on the
remote control for even better
control of your TransMix!



Technical data

Pump	Pneumatic air conveyor
Drive motor	Diesel, Kubota, 55.4 kW (Stage V)
Delivery pressure	Max. 10 bar
Delivery output	Up to 6 m³/h
Mixing container	260 l
Conveying distance	Up to 180 m wide, up to 90 m high
Maximum particle size	16 mm
Weight (empty)	Approx. 12.5 t (without towing vehicle)
Aggregate binder volume	Approx. 19 m³ / 6 m³
Trough size	25 m³
Water loading	120 l (2 x 60 l)
Dimensions (L x W x H)	11.4 m x 2.5 m x 3.7 m
Loading height for surcharge quantity	3.4 m

* The delivery output is theoretic and depends on the
type of worm pump

** Information is based on experience and depends on the
material

Our service team – only the best for your TransMix

Our TransMix service is just as first-class as our machines when it comes to consulting, maintenance, repairs, and spare parts procurement.

Our professionals are available to quickly arrive at your location and assist with any technical questions.

TransMix service hotline: +49 7127 599-699 • Mail: mm@putzmeister.com

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
P.O.Box 2152 · 72629 Aichtal / Germany
Tel. +49 7127 599-0 · Fax +49 7127 599-743
mm@putzmeister.com · www.putzmeister.com

